



AIRPREP SYSTEMS

Proven to boost productivity, reduce rusting, prevent clogged blast pots, keep abrasives free-flowing

A product of Axxiom Manufacturing, Inc.

Behind insufficient air supply, moisture is the second largest enemy to blasting productivity. Wet air causes flash rusting, clogs blast pots with damp abrasives, damages control valves and reduces blasting productivity. Blasting operations that simply add a Schmidt® AirPrep System have documented increased production of 12 to 15%.

AirPrep Systems are designed to cool and dry compressed air used in abrasive blasting equipment. Compressed air enters a pre-filter that removes contaminants and condensed moisture. The air then travels through a fan-cooled radiator, where it is cooled to cause moisture to condense. The cooled air and water droplets flow into a separator tank, where the air expands and causes further condensation. The spinning movement of the air stream separates out the condensed moisture.

Schmidt AirPrep Systems stand alone in the industry: they are manufactured to provide the highest levels of air treating capability with extremely low pressure drops. Available in your choice of aftercoolers or air dryers.



Air Dryer System (ADS)



Aftercooler System (ACS)

FEATURES

- Compact, vertical air flow design to improve efficiency
- Pneumatic fan motor. Includes filter, regulator, lubricator and muffler (electric fan available)
- Protective bar grating
- Portable or stationary units
- Easy transport. Skid mounted (excludes portable options) with forklift pockets and full load lifting eyes

AIR DRYERS

- Maximum performance systems for maximum air treatment
- Ideal for high humidity environments or when moisture removal is critical
- Multistep filtration: inlet filter captures debris, outlet filter screens errant small particles
- Built to last—hot-dipped galvanized to prevent internal rusting

AFTERCOOLERS

- High performance systems
- Inlet prefilter removes oil, debris and contaminants

Sizes available:

250, 400, 750, 950, 1200, 1600, 2000 and 2500 cfm

(images shown are for 1600 model)

800-231-2085
AXXIOMMFG.COM



ABOUT THE AIRPREPS

AFTERCOOLER SYSTEM (ACS)

In the Aftercooler System (ACS), the air rises through a stainless steel particulate filter that attracts condensed moisture. Removed moisture is collected in the bottom of the separator tank. The dryer, cooler air then exits the tank for use in the abrasive blasting operation.

AIR DRYER SYSTEM (ADS)

In the Air Dryer System (ADS), the air rises through a bed of marbles and into deliquescent/dessicant tablets inside the tank before the air exits the vessel. Approximately 50% of residual moisture is removed (after cooling). Removed moisture is collected in the bottom of the separator tank. An after-filter removes particulates that may have become airborne, then used in the abrasive blasting operation.

AIRPREP SPECIFICATIONS

Maximum Working Pressure:

150 psig at 250 °F (10.3 bar at 121 °C)

Minimum Operating Temperature:

35 °F at 150 psig (1.7 °C at 10.3 bar)

Moisture Removal (ACS):

Stainless steel coalescent filter

Moisture Removal (ADS):

Deliquescent tablets (not included) with glass marble bed

VIDEOS

See videos on the AirPrep family on our website and YouTube.

MODEL (CFM)	VOLUME/ AIR DRYER DELIQUESCENT STORAGE – CU FT (L)	INLETS/OUTLETS (NPT) (x) = NO. of OUTLETS	DIMENSIONS L x W x H IN (CM)	WEIGHT LBS (KG)
ACS 250P	2.7 (77)	2" / (1) 2", (2) 1½"	35 x 24 x 54* (89 x 61 x 137*)	370 (138)
ACS 400P	2.7 (77)	2" / (1) 2", (2) 1½"	35 x 24 x 58* (89 x 61 x 147*)	432 (161)
ACS 400	8.7 (244)	2" / (1) 2", (2) 1½", (4) 1"	49 x 30 x 67* (124 x 76 x 170*)	711 (265)
ACS 750	10.0 (283)	2" / (1) 2", (2) 1 1/2", (4) 1"	57 x 30 x 73* (145 x 76 x 185*)	793 (296)
ACS 950	10.2 (289)	3" / (1) 3", (2) 2", (4) 1"	68 x 35 x 85* (173 x 89 x 216*)	1220 (455)
ACS 1200	10.2 (289)	3" / (1) 3", (2) 2", (4) 1"	72 x 35 x 85* (183 x 89 x 216*)	1286 (480)
ACS 1600	10.2 (634)	3" / (1) 3", (2) 2", (4) 1"	74 x 37 x 85* (188 x 94 x 216*)	1572 (587)
ACS 2000	37.0 (1048)	4" / (1) 4", (2) 2", (2) 1"	80 x 40 x 98* (203 x 102 x 249*)	2105 (957)
ACS 2500	37.0 (1048)	4" / (1) 4", (2) 2", (2) 1"	116 x 49 x 80* (295 x 124 x 203*)	2365 (1075)
ADS 250P	2.7/1.5 (77/42)	2" / (1) 2"	35 x 24 x 52* (89 x 61 x 132*)	398 (148)
ADS 400P	2.7/1.5 (77/42)	2" / (1) 2"	35 x 24 x 58* (89 x 61 x 147*)	424 (158)
ADS 400	8.5/6.0 (240/170)	2" / (1) 2", (2) 1"	49 x 30 x 68* (124 x 76 x 173*)	848 (316)
ADS 750	11.7/8.0 (332/226)	2" / (1) 2", (2) 1"	57 x 30 x 82* (145 x 76 x 208*)	965 (360)
ADS 950	11.7/8.0 (332/226)	3" / (1) 3", (2) 1"	68 x 35 x 92* (173 x 89 x 234*)	1489 (556)
ADS 1200	11.7/8.0 (332/226)	3" / (1) 3", (2) 1"	72 x 35 x 92* (183 x 89 x 234*)	1524 (570)
ADS 1600	19.0/17.0 (538/481)	3" / (1) 3", (2) 1"	76 x 37 x 95* (193 x 94 x 241*)	2055 (767)
ADS 2000	40. 3/20.0 (1141/566)	4" / (1) 4", (2) 1"	87 x 43 x 99+ (221 x 109 x 251+)	2600 (970)
ADS 2500	45.0/25.0 (1274/708)	4" / (1) 4", (2) 1"	116 x 49 x 80+ (295 x 124 x 203+)	3080 (1150)

Contact your local Schmidt distributor or call Axxiom at 800-231-2085 for distributor information.

Axxiom Manufacturing, Inc. is the manufacturer of Schmidt products. Certain products manufactured by Axxiom are protected by patents and pending applications in the United States and globally. Unless specified otherwise, all trademarks are the exclusive property of Axxiom Manufacturing, Inc. © 2021. All rights reserved.

800-231-2085
AxxiomMfg.COM

